



Model	Indoor Unit		SEZ-KD09NA4
	Outdoor Unit		SUZ-KA09NA
Capacity (Rated)	Cooling	Btu/h	8,100
Capacity (Min. ~ Max.)		Btu/h	3,800 ~ 10,900
Capacity (Rated)	Heating @ 47°F	Btu/h	10,900
Capacity (Min. ~ Max.)		Btu/h	4,800 ~ 14,100
Capacity	Heating @ 17°F	Btu/h	7,300
Power Consumption (Total Input)	Cooling	W	670
	Heating @ 47°F	W	1,020
	Heating @ 17°F	W	1,000
EER	Cooling		12.0
SEER	Cooling		15.0
HSPF (IV)	Heating		10.0
Capacity Control	Variable Speed Compressor (VCSi)		
Refrigerant	R-410A		
Power Supply	V, Phase, Hz		208/230, 1, 60
Moisture Removal	Pints/h		1.5
External Static Pressure	in. WG (Pa)		0.02-0.06-0.14-0.20 (5-15-35-50)
Airflow (Low-Med-Hi)	CFM Dry		194-247-317
Sound Indoor (Low-Med-Hi)	Cooling	dB(A)	23-26-30
Sound Outdoor	Cooling	dB(A)	46
Max. Fuse Size (Time Delay)	Indoor	A	15
	Outdoor	A	15
	Outdoor	A	12
Min. Ampacity	Indoor	A	1.0
	Outdoor	A	12
Fan Speed Control	4 (Auto, Hi, Med, Low)		
Air Filters (Washable)	PP Honeycomb Fabric		
Dimensions (H x W x D)	Indoor	in.	7-7/8 x 31-1/8 x 27-9/16
	Outdoor	in.	21-5/8 x 31-1/2 x 11-1/4
Weight	Indoor	lbs.	42
	Outdoor	lbs.	66
Pipe Size	Liq. X Gas	in.	1/4 x 3/8
Max. Height Difference		ft.	40
Max. Pipe Length		ft.	65
Outdoor Operating Range	Cooling		14 – 115°FDB
	Heating		-4 – 75°FDB (-5 – 65°FDB)

THIS SYMBOL DENOTES AN ENERGY STAR-CERTIFIED UNIT

Single ceiling-concealed split systems



VCSi
TECHNOLOGY



Optional accessories available.
Visit www.mrslim.ca for more information.

Heat pump

- Variable Compressor Speed Inverter Technology
- Ozone-Friendly R-410A Refrigerant
- Significant Energy Savings (up to 30%)
- Auto Change Over Between Cooling & Heating
- Extreme Quiet Operation – as low as 23dB(A)
- Ultra-Thin Profile – only 7-7/8 in. high
- Adjustable ESP to meet different layouts
- Built-in High-Performance Drain Pump
- Long Pipe Runs – Up to 100 ft.
- Low Ambient Heating -20°C/-4°F
- Refrigerant Pre-Charged
- 5-Year Parts Warranty
- 7-Year Compressor Warranty

SEZ-KD12NA4 ★	SEZ-KD15NA4 ★	SEZ-KD18NA4 ★
SUZ-KA12NA	SUZ-KA15NA	SUZ-KA18NA
11,500	14,100	17,200
3,800 ~ 13,300	3,800 ~ 17,000	3,800 ~ 19,000
13,600	18,000	21,600
4,800 ~ 16,400	4,800 ~ 21,100	4,800 ~ 24,900
9,800	13,700	15,000
920	1,170	1,380
1,140	1,500	1,700
1,180	1,650	1,830
12.5	12.0	12.5
16.0	15.5	17.5
10.0	10.0	10.0
Variable Speed Compressor (VCSi)	Variable Speed Compressor (VCSi)	Variable Speed Compressor (VCSi)
R-410A	R-410A	R-410A
208/230, 1, 60	208/230, 1, 60	208/230, 1, 60
2.4	2.6	3.4
0.02-0.06-0.14-0.20 (5-15-35-50)	0.02-0.06-0.14-0.20 (5-15-35-50)	0.02-0.06-0.14-0.20 (5-15-35-50)
247-317-388	353-441-529	423-529-635
23-28-33	30-34-37	30-34-38
49	49	54
15	15	15
15	15	15
1.0	1.0	1.0
12	12	14
4 (Auto, Hi, Med, Low)	4 (Auto, Hi, Med, Low)	4 (Auto, Hi, Med, Low)
PP Honeycomb Fabric	PP Honeycomb Fabric	PP Honeycomb Fabric
7-7/8 x 39 x 27-9/16	7-7/8 x 39 x 27-9/16	7-7/8 x 46-7/8 x 27-9/16
21-5/8 x 31-1/2 x 11-1/4	21-5/8 x 31-1/2 x 11-1/4	33-7/16 x 33-1/16 x 13
50	54	62
77	80	119
1/4 x 3/8	1/4 x 1/2	1/4 x 1/2
40	40	50
65	65	100
14 – 115°FDB	14 – 115°FDB	14 – 115°FDB
-4 – 75°FDB (-5 – 65°FDB)	-4 – 75°FDB (-5 – 65°FDB)	-4 – 75°FDB (-5 – 65°FDB)

All test conditions are based on ARI 210/240.
Rating conditions: Cooling – Indoor: 80°FDB, 67°FWB; Outdoor: 95°FDB, 75°FWB; Rated frequency
Heating – Indoor: 70°FDB, 60°FWB; Outdoor: 47°FDB, 43°FWB; Rated frequency