

FUJITSU

SINGLE ZONE COMPACT CASSETTES
9, 12 & 18,000 BTU • 9RLFCC, 12RLFCC, 18RLFCC

UP TO 24 SEER



*For over 35 years, we strive to make
your environment more comfortable!*




SINGLE ZONE COMPACT CASSETTES

9, 12 & 18,000 BTU • 9RLFCC, 12RLFCC, 18RLFCC

UP TO 24 SEER

HIGH PERFORMANCE HEATING

Heating capacity at low outdoor temperatures is achieved by adopting a large heat exchanger and a high capacity compressor. Systems operate down to -21°C.



STANDARD FEATURES

- wired remote control ~
- sleep timer ~
- dry mode ~
- auto louver: up/ down ~
- quiet mode ~
- auto restart/reset ~
- remote temperature sensor ~
- high ceiling mode ~
- condensate pump ~
- 2-stage turbo fan ~
- minimum heat mode+ ~
- fresh air intake** ~

EASY INSTALLATION

Fits into a standard ceiling tile*.



*Dimensions of outer grille are 27-9/16" x 27-9/16" and may overlap adjacent tiles.

+ Available only with optional wireless remote control.

* Compact cassette grille UTG-CCGF sold separately. Must order one with each compact cassette.

** Requires Fujitsu's optional fresh air kit part #UTZ-VXAA. Allows for a 4-inch flex duct connection.

Requires a field supplied duct booster fan capable of 60 CFM at .2" W.C. or 90 CFM at .4" W.C.

	9RLFCC	12RLFCC	18RLFCC
Nominal Cooling BTU/h	9,000	12,000	18,000
Min~Max Cooling BTU/h	3,100~12,000	3,100~13,600	3,100~20,100
Nominal Heating BTU/h	12,000	16,000	21,600
Min~Max Heating BTU/h	3,100~22,000	3,100~22,100	3,100~25,600
HSPF	13.0	12.2	11.5
SEER	24.0	21.9	20.1
EER Clg/Htg	14.5/13.5	12.8/11.1	11.2/12.3
Cooling Operating Range °F(°C)	14~115 (-10~46)	14~115 (-10~46)	14~115 (-10~46)
Heating Operating Range °F(°C)	-5~75 (-21~24)	-5~75 (-21~24)	-5~75 (-21~24)
Moisture Removal Pt./h(l/h)	0.6 (1.3)	1.2 (2.5)	2.2 (4.6)
Voltage/Frequency/Phase	208-230/60/1	208-230/60/1	208-230/60/1
Recommended Fuse Size (A)	15	15	20
Air Circ. C.F.M. (m ³ /h): Hi	318 (540)	359 (610)	400 (680) 471 (800)
Medium	288 (490)	312 (530)	341 (580) 400 (680)
Low	259 (440)	277 (470)	288 (490) 341 (580)
Quiet	230 (390)	241 (410)	241 (410) 265 (450)
Noise Level dB(A) Clg/Htg: Hi	33/34	37/37	40/44
Medium	31/32	33/33	36/40
Low	29/29	31/31	32/36
Quiet	27/27	28/28	28/30
Outdoor Fan Speed RPM Clg/Htg	590/720	870/780	1,050/1,000
Outdoor Noise Level Clg/Htg	48/49	49/50	54/55
Running Current Rated (A): Cooling	2.7	4.1	7.1
Heating	3.9	6.3	7.7
Power Use Rated/Max (kW): Clg	0.62/2.12	0.94/2.14	1.61/2.28
Heating	0.89/2.46	1.44/2.48	1.76/3.19
Fan Speeds Stage	4+auto	4+auto	4+auto
Air Direction: Vertical	Automatic	Automatic	Automatic
Air Filter	Washable	Washable	Washable
Front Grille	UTG-CCGF*	UTG-CCGF*	UTG-CCGF*
Connection Method	Flare	Flare	Flare
Conn. Pipe Diameter Inch	suc 3/8 dis 1/4	suc 3/8 dis 1/4	suc 1/2 dis 1/4
Indoor Unit Net Weight lbs. (kg)	33 (15)	33 (15)	33 (15)
Outdoor Unit Net Weight lbs. (kg)	84 (38)	84 (38)	86 (39)
Indoor Unit Dim: Height Inch (mm)	9-11/16 (245)	9-11/16 (245)	9-11/16 (245)
Width Inch (mm)	22-7/16 (570)	22-7/16 (570)	22-7/16 (570)
Depth Inch (mm)	22-7/16 (570)	22-7/16 (570)	22-7/16 (570)
Grille Dim: Height Inch (mm)	1-15/16 (49)	1-15/16 (49)	1-15/16 (49)
Width Inch (mm)	27-9/16 (700)	27-9/16 (700)	27-9/16 (700)
Depth Inch (mm)	27-9/16 (700)	27-9/16 (700)	27-9/16 (700)
Outdoor Unit Dim: Height Inch (mm)	24-1/2 (620)	24-1/2 (620)	24-1/2 (620)
Width Inch (mm)	31-3/32 (790)	31-3/32 (790)	31-3/32 (790)
Depth Inch (mm)	11-11/32 (290)	11-11/32 (290)	11-11/32 (290)



authorized dealer



Proper sizing and installation of equipment is critical to achieve optimal performance. Split system air conditioners and heat pumps must be matched with appropriate coil components to meet ENERGY STAR criteria. Ask your contractor for details or visit www.energystar.gov.

